

PATENT COOPERATION TREATY
PCT
INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference 2224990/PHH/JCC/TJL	FOR FURTHER ACTION	See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416).
International application No. PCT/AU99/00940	International filing date (<i>day/month/year</i>) 29 October 1999	Priority Date (<i>day/month/year</i>) 4 November 1998
International Patent Classification (IPC) or national classification and IPC Int. Cl. ⁷ F42B 3/195, 3/12, 3/14, 3/16; C06C 7/02		
Applicant ORICA EXPLOSIVES TECHNOLOGY PTY LTD et al		

1.	This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.																								
2.	<p>This REPORT consists of a total of 3 sheets, including this cover sheet.</p> <p><input checked="" type="checkbox"/> This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).</p> <p>These annexes consist of a total of 15 sheet(s).</p>																								
3.	<p>This report contains indications relating to the following items:</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 5%;">I</td> <td style="width: 5%;"><input checked="" type="checkbox"/></td> <td>Basis of the report</td> </tr> <tr> <td>II</td> <td><input type="checkbox"/></td> <td>Priority</td> </tr> <tr> <td>III</td> <td><input type="checkbox"/></td> <td>Non-establishment of opinion with regard to novelty, inventive step and industrial applicability</td> </tr> <tr> <td>IV</td> <td><input type="checkbox"/></td> <td>Lack of unity of invention</td> </tr> <tr> <td>V</td> <td><input checked="" type="checkbox"/></td> <td>Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement</td> </tr> <tr> <td>VI</td> <td><input type="checkbox"/></td> <td>Certain documents cited</td> </tr> <tr> <td>VII</td> <td><input type="checkbox"/></td> <td>Certain defects in the international application</td> </tr> <tr> <td>VIII</td> <td><input type="checkbox"/></td> <td>Certain observations on the international application</td> </tr> </table>	I	<input checked="" type="checkbox"/>	Basis of the report	II	<input type="checkbox"/>	Priority	III	<input type="checkbox"/>	Non-establishment of opinion with regard to novelty, inventive step and industrial applicability	IV	<input type="checkbox"/>	Lack of unity of invention	V	<input checked="" type="checkbox"/>	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement	VI	<input type="checkbox"/>	Certain documents cited	VII	<input type="checkbox"/>	Certain defects in the international application	VIII	<input type="checkbox"/>	Certain observations on the international application
I	<input checked="" type="checkbox"/>	Basis of the report																							
II	<input type="checkbox"/>	Priority																							
III	<input type="checkbox"/>	Non-establishment of opinion with regard to novelty, inventive step and industrial applicability																							
IV	<input type="checkbox"/>	Lack of unity of invention																							
V	<input checked="" type="checkbox"/>	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement																							
VI	<input type="checkbox"/>	Certain documents cited																							
VII	<input type="checkbox"/>	Certain defects in the international application																							
VIII	<input type="checkbox"/>	Certain observations on the international application																							

Date of submission of the demand 9 March 2000	Date of completion of the report 12 July 2000
Name and mailing address of the IPEA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaaustralia.gov.au Facsimile No. (02) 6285 3929	Authorized Officer JEFFREY CARL Telephone No. (02) 6283 2543

I. Basis of the report1. With regard to the **elements** of the international application:*

- ☐ the international application as originally filed.
- ☒ the description, pages **2-4, 7-10, 12, 14-16, 19-30**, as originally filed,
pages , filed with the demand,
pages **1-1A, 5-6, 11, 13, 17-18A**, received on **26 May 2000** with the letter of **26 May 2000**
- ☒ the claims, pages , as originally filed,
pages , as amended (together with any statement) under Article 19,
pages , filed with the demand,
pages **31-35**, received on **26 May 2000** with the letter of **26 May 2000**
page **36**, received on **5 July 2000** with the letter of **4 July 2000**
- ☒ the drawings, pages **1/3-3/3**, as originally filed,
pages , filed with the demand,
pages , received on with the letter of
- ☐ the sequence listing part of the description:
pages , as originally filed
pages , filed with the demand
pages , received on with the letter of

2. With regard to the **language**, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.

These elements were available or furnished to this Authority in the following language which is:

- ☐ the language of a translation furnished for the purposes of international search (under Rule 23.1(b)).
- ☐ the language of publication of the international application (under Rule 48.3(b)).
- ☐ the language of the translation furnished for the purposes of international preliminary examination (under Rules 55.2 and/or 55.3).

3. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, was on the basis of the sequence listing:

- ☐ contained in the international application in written form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

4. ☐ The amendments have resulted in the cancellation of:

- ☐ the description, pages
- ☐ the claims, Nos.
- ☐ the drawings, sheets/fig.

5. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).**

* Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17).

** Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**1. Statement**

Novelty (N)	Claims 1-34	YES
	Claims	NO
Inventive step (IS)	Claims 1-34	YES
	Claims	NO
Industrial applicability (IA)	Claims 1-34	YES
	Claims	NO

2. Citations and explanations (Rule 70.7)

Claims 1-34: The amended claims relate to detonators (claims 1-28), an initiating element (claim 29), a process for manufacturing a detonator (claims 30-32), a method of blasting using a detonator (claim 33) and a composition for use in an explosive detonator (claim 34), all characterised by the composition comprising an intimate mixture of a relatively large particle size, porous powdered explosive having interstitial spaces, and a relatively small particle size high burn-rate pressurising initiator located in said interstitial spaces.

No individual citation or obvious combination of citations disclose detonators, initiating elements, processes or methods characterised by a composition as defined in the amended claims.

The closest art of US 4156390 relates to an electrically operated igniter for a detonator. The igniter includes an intimate binary composition of primary explosive (lead azide) with an average particle size of 30 μm and graphite with an average particle size of 9 μm . The purpose of the graphite in the composition is to conduct electricity, not to act as a pressurising initiator as is defined in the composition of the present invention. Also, there is no indication in this document that the graphite could be replaced by a substance that would act as a high burn-rate pressurising initiator.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU 99/00940

A. CLASSIFICATION OF SUBJECT MATTER		
Int Cl ⁶ : F42B 3/195, 3/12, 3/14, 3/16; C06C 7/02		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
IPC F42B 3/10, 3/195, 3/12, 3/14, 3/16; C06C 7/00, 7/02		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
AU IPC as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
WPAT with keywords		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4156390 A (FERGUSON et al) 29 May 1979 Column 4, lines 8-19	1-3, 5-9, 11-12, 14-15, 18-21, 23-27, 29-30, 33
Y	Column 4, lines 8-19	1-33
Y	AU 73573/98 A (THE ENSIGN-BICKFORD COMPANY) 30 October 1998 Whole document	1-33
<input type="checkbox"/> Further documents are listed in the continuation of Box C <input checked="" type="checkbox"/> See patent family annex		
<p>* Special categories of cited documents:</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>		
Date of the actual completion of the international search 17 November 1999		Date of mailing of the international search report
Name and mailing address of the ISA/AU AUSTRALIAN PATENT OFFICE PO BOX 200 WODEN ACT 2606 AUSTRALIA Facsimile No.: (02) 6285 3929		Authorized officer JEFFREY CARL Telephone No.: (02) 6283 2543

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU 99/00940

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
AU	73573/98	WO	98/45663	US	5889228	ZA	9802987
<p>END OF ANNEX</p>							

PATENT COOPERATION TREATY

FRI 17 APR 2000

PCT

NOTIFICATION OF THE RECORDING
OF A CHANGE(PCT Rule 92bis.1 and
Administrative Instructions, Section 422)

From the INTERNATIONAL BUREAU

To:

HUNTSMAN, Peter, Harold
Davies Collison Cave
1 Little Collins Street
Melbourne, VIC 3000
AUSTRALIE

PHH

Date of mailing (day/month/year) 08 March 2000 (08.03.00)	IMPORTANT NOTIFICATION
Applicant's or agent's file reference 2224990/PHH	
International application No. PCT/AU99/00940	International filing date (day/month/year) 29 October 1999 (29.10.99)

Orica Explosives

1. The following indications appeared on record concerning:		
<input checked="" type="checkbox"/> the applicant	<input checked="" type="checkbox"/> the inventor	<input type="checkbox"/> the agent
<input type="checkbox"/> the common representative		
Name and Address CHAN, Sek, Kwan 293 Frobisher Street St. Bruno, Quebec J3V 2N8 Canada	State of Nationality CA	State of Residence CA
	Telephone No.	
	Facsimile No.	
	Teleprinter No.	
2. The International Bureau hereby notifies the applicant that the following change has been recorded concerning:		
<input type="checkbox"/> the person	<input type="checkbox"/> the name	<input checked="" type="checkbox"/> the address
<input type="checkbox"/> the nationality		
<input type="checkbox"/> the residence		
Name and Address CHAN, Sek, Kwan 4076 Kuchiran Street Pierrefonds Quebec, H9H 4A9 Canada	State of Nationality CA	State of Residence CA
	Telephone No.	
	Facsimile No.	
	Teleprinter No.	
3. Further observations, if necessary:		
4. A copy of this notification has been sent to:		
<input checked="" type="checkbox"/> the receiving Office	<input type="checkbox"/> the designated Offices concerned	
<input type="checkbox"/> the International Searching Authority	<input type="checkbox"/> the elected Offices concerned	
<input type="checkbox"/> the International Preliminary Examining Authority	<input type="checkbox"/> other:	

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland	Authorized officer Maria Victoria CORTIELLO
Facsimile No.: (41-22) 740.14.35	Telephone No.: (41-22) 338.83.38

PCT REQUESTOriginal (for **SUBMISSION**) - printed on 04.11.1999 02:19:31 PM

0	For receiving Office use only	
0-1	International Application No.	
0-2	International Filing Date	
0-3	Name of receiving Office and "PCT International Application"	
0-4	Form - PCT/RO/101 PCT Request Prepared using	PCT-EASY Version 2.84 (updated 01.07.1999)
0-5	Petition The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty	
0-6	Receiving Office (specified by the applicant)	Australian Patent Office (RO/AU)
0-7	Applicant's or agent's file reference	2224990/PHH
I	Title of invention	NON-PRIMARY DETONATORS
II	Applicant	
II-1	This person is:	applicant only
II-2	Applicant for	all designated States except US
II-4	Name	ORICA EXPLOSIVES TECHNOLOGY PTY LTD
II-5	Address:	- 1 Nicholson Street Melbourne, Victoria 3000 Australia
II-6	State of nationality	AU
II-7	State of residence	AU
II-8	Telephone No.	-
II-9	Facsimile No.	-
II-10	e-mail	-
III-1	Applicant and/or inventor	
III-1-1	This person is:	applicant and inventor
III-1-2	Applicant for	US only
III-1-4	Name (LAST, First)	COOPER, John
III-1-5	Address:	- 11 Lamford Drive Ayr Scotland, KA7 4DE United Kingdom
III-1-6	State of nationality	GB
III-1-7	State of residence	GB

PCT REQUEST

Original (for SUBMISSION) - printed on 04.11.1999 02:19:31 PM

III-2	Applicant and/or inventor	
III-2-1	This person is:	applicant and inventor
III-2-2	Applicant for	US only
III-2-4	Name (LAST, First)	SUTTON, David, Proven
III-2-5	Address:	- 8 Peacocks Close Stokesley North Yorkshire, TS9 5QD United Kingdom
III-2-6	State of nationality	GB
III-2-7	State of residence	GB
III-3	Applicant and/or inventor	
III-3-1	This person is:	applicant and inventor
III-3-2	Applicant for	US only
III-3-4	Name (LAST, First)	CHAN, Sek, Kwan
III-3-5	Address:	- 293 Frobisher Street St. Bruno, Québec J3V 2N8 Canada
III-3-6	State of nationality	CA
III-3-7	State of residence	CA
IV-1	Agent or common representative; or address for correspondence	
	The person identified below is hereby/has been appointed to act on behalf of the applicant(s) before the competent International Authorities as:	agent
IV-1-1	Name (LAST, First)	HUNTSMAN, Peter, Harold
IV-1-2	Address:	Davies Collison Cave 1 Little Collins Street Melbourne, Victoria 3000 Australia
IV-1-3	Telephone No.	+61-3-9254 2777
IV-1-4	Facsimile No.	+61-3-9254 2770
IV-1-5	e-mail	mail@davies.com.au
IV-2	Additional agent(s)	additional agent(s) with same address as first named agent
IV-2-1	Name(s)	ANGLISS, Michael; CAINE, Michael
V	Designation of States	
V-1	Regional Patent (other kinds of protection or treatment, if any, are specified between parentheses after the designation(s) concerned)	--
V-2	National Patent (other kinds of protection or treatment, if any, are specified between parentheses after the designation(s) concerned)	AU CA CN US ZA ZW

PCT REQUEST

2224990/PHH

Original (for SUBMISSION) - printed on 04.11.1999 02:19:31 PM

V-5	Precautionary Designation Statement In addition to the designations made under items V-1, V-2 and V-3, the applicant also makes under Rule 4.9(b) all designations which would be permitted under the PCT except any designation(s) of the State(s) indicated under item V-6 below. The applicant declares that those additional designations are subject to confirmation and that any designation which is not confirmed before the expiration of 15 months from the priority date is to be regarded as withdrawn by the applicant at the expiration of that time limit.	
V-6	Exclusion(s) from precautionary designations	NONE
VI-1	Priority claim of earlier national application	
VI-1-1	Filing date	04 November 1998 (04.11.1998)
VI-1-2	Number	2,252,353
VI-1-3	Country	CA
VI-2	Priority claim of earlier national application	
VI-2-1	Filing date	19 August 1999 (19.08.1999)
VI-2-2	Number	PQ2315
VI-2-3	Country	AU
VI-3	Priority document request The receiving Office is requested to prepare and transmit to the International Bureau a certified copy of the earlier application(s) identified above as item(s):	VI-2
VII-1	International Searching Authority Chosen	Australian Patent Office (ISA/AU)
VII-2	Request to use results of earlier search; reference to that search	
VII-2-1	Date	04 October 1999 (04.10.1999)
VII-2-2	Number	99/1651
VII-2-3	Country (or regional Office)	AU
VIII	Check list	number of sheets electronic file(s) attached
VIII-1	Request	4 -
VIII-2	Description	30 -
VIII-3	Claims	6 -
VIII-4	Abstract	1 2224990.txt
VIII-5	Drawings	3 -
VIII-7	TOTAL	44
	Accompanying items	paper document(s) attached electronic file(s) attached
VIII-8	Fee calculation sheet	✓ -
VIII-16	PCT-EASY diskette	- diskette
VIII-18	Figure of the drawings which should accompany the abstract	-
VIII-19	Language of filing of the international application	English

PCT REQUEST

2224990/PHH

Original (for SUBMISSION) - printed on 04.11.1999 02:19:31 PM

IX-1	Signature of applicant or agent	
IX-1-1	Name (LAST, First)	CAINE, Michael

FOR RECEIVING OFFICE USE ONLY

10-1	Date of actual receipt of the purported international application	
10-2	Drawings:	
10-2-1	Received	
10-2-2	Not received	
10-3	Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application	
10-4	Date of timely receipt of the required corrections under PCT Article 11(2)	
10-5	International Searching Authority	ISA/AU
10-6	Transmittal of search copy delayed until search fee is paid	

FOR INTERNATIONAL BUREAU USE ONLY

11-1	Date of receipt of the record copy by the International Bureau	
------	--	--

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F42B 3/195, 3/12, 3/14, 3/16, C06C 7/02		A1	(11) International Publication Number: WO 00/26603
			(43) International Publication Date: 11 May 2000 (11.05.00)
(21) International Application Number: PCT/AU99/00940			(81) Designated States: AU, CA, CN, US, ZA, ZW. Published <i>With international search report.</i>
(22) International Filing Date: 29 October 1999 (29.10.99)			
(30) Priority Data: 2,252,353 4 November 1998 (04.11.98) CA PQ 2315 19 August 1999 (19.08.99) AU			
(71) Applicant (for all designated States except US): ORICA EXPLOSIVES TECHNOLOGY PTY. LTD. [AU/AU]; 1 Nicholson Street, Melbourne, VIC 3000 (AU).			
(72) Inventors; and (75) Inventors/Applicants (for US only): COOPER, John [GB/GB]; 11 Lamford Drive, Ayr, Scotland KA7 4DE (GB). SUTTON, David, Proven [GB/GB]; 8 Peacocks Close, Stokesley, North Yorkshire TS9 5QD (GB). CHAN, Sek, Kwan [CA/CA]; 4076 Kuchiran Street, Pierrefonds, Quebec H9H 4A9 (CA).			
(74) Agents: HUNTSMAN, Peter, Harold et al.; Davies Collison Cave, 1 Little Collins Street, Melbourne, VIC 3000 (AU).			

(54) Title: **NON-PRIMARY DETONATORS**

(57) Abstract

Deflagration to detonation transition (DDT) detonators (1) are provided which are essentially free from primary explosives. Detonators (1) utilise an intimate mixture (5) of a large particle sized porous, powdered explosive such as PETN, and a smaller particle size, high-burn-rate, pressurising initiator such as a mixture of potassium picrate and potassium perchlorate. The smaller particle sized pressurising initiator is located within the interstitial spaces of the larger powdered explosive. Mixture (5) is able to reliably initiate an adjacent transition portion (4), or base charge (2) while reducing the need for heavy confinement. Mixture (5) can also be used directly in surface detonator applications. Improved performance and safety during manufacture of detonators is achieved.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Non-primary DetonatorsField of the Invention

The present invention relates to explosive detonators comprising compositions which are characterized by being essentially free from molecular
5 primary explosives.

Description of the Related Art

Detonators, including electronic, electric and non-electric types, are widely employed in mining, quarrying and other blasting operations. In-hole detonators are generally used to initiate an explosive charge which has been placed in a
10 borehole, while surface detonators are generally used outside of the borehole to initiate one or more explosive initiating signal means such as shock tube or detonating cord.

Modern commercial detonators typically comprise, in the case of an in-hole detonator, a metallic shell which is closed at one end and which contains, in
15 sequence from the closed end, a base charge of a detonating, secondary explosive, such as for example, pentaerythritoltetranitrate (PETN), and a primer charge of a heat-sensitive, detonable, primary explosive, such as for example, lead azide, which is above and adjacent to the base charge. In a delay detonator, adjacent the primary explosive is an amount of a deflagrating or burning
20 composition of sufficient quantity to provide a desired delay time. Above the delay composition (if present) is an electric match, a low energy detonating cord or shock wave conductor (such as shock tube), or the like, retained in the open end of the metallic shell.

Surface detonators are generally identical to in-hole detonators with the
25 exception that the base charge of high explosive is preferably reduced or omitted to give lower output. The output is preferably reduced to a level sufficient to initiate adjacent shock tube, detonating cord and the like, without, for example,

throwing excessive amounts of shrapnel which can damage nearby lengths of shock tube or cord. This feature of output control is a desirable practise in the design of detonators in order to control the energy output of in-hole and surface detonators.

5 For the purposes of this specification, a primary explosive is defined as an explosive substance which readily develops complete detonation from stimuli such as flame, conductive heating, impact, friction or static electrical discharge, even in the absence of any confinement. In contrast, a secondary explosive can generally only be detonated if it is present in larger quantities or if contained
10 within heavy confinement such as a heavy walled metal container, or by being exposed to significant shock wave or mechanical impact. Examples of primary explosives are mercury fulminate, lead styphnate, lead azide and diazodinitrophenol (DDNP) or mixtures of two or more of these and/or similar substances. Representative examples of secondary explosives are (PETN),
15 cyclotrimethylenetrinitramine (RDX), cyclotetramethylenetetranitramine (HMX), trinitrophenylmethylnitramine (Tetryl) and trinitrotoluene (TNT) or mixtures of two or more of these and/or other similar substances.

The use of lead azide as a heat-sensitive, primary explosive material, or as the sole component of the base charge (in the case of some surface detonator
20 type initiators), is standard practice in the detonator industry. Accordingly, primary explosives, and in particular lead azide, are widely used by this industry.

This use of primary explosives in the preparation of surface and in-hole detonators, and in particular, the use of lead-containing materials such as lead azide, has several serious disadvantages. These include, for example, (i) that
25 even the presence of a small charge of primary explosive makes a conventional detonator potentially hazardous to handle because of its sensitivity to mechanical deformation or impact; (ii) that the manufacture of the detonator requires the production and handling of significant quantities of sensitive materials which require costly handling procedures; and (iii) that detonator manufacturing plants
30 must address the health risks of dealing with potentially toxic materials such as lead, and address the proper disposal of these toxic materials.

Accordingly, due to the desirability of minimizing or eliminating the use of primary explosives during the production and use of detonators, for, inter alia, safety and/or toxicity reasons, it would be desirable to provide a detonator which was essentially free from primary explosives, and in particular, lead azide.

5 One approach to the elimination of primary explosives from detonators has been the development of primary explosive-free detonators which rely on the establishment of conditions in the detonator which will cause a secondary explosive to undergo a "deflagration to detonation transition" (DDT) reaction. In these DDT detonators, a deflagration reaction is typically initiated in a secondary
10 explosive by a thermal reaction with an igniting device, such as the flame front from a shock tube, or directly from a heated bridge wire. By suitable confinement of the secondary explosive, and/or control of the secondary explosive particle size, morphology, density, and formulation, as well as careful selection of the initiation means and detonator design, this deflagration reaction is caused to
15 transfer to a detonation reaction which detonation provides sufficient force to initiate an adjacent base charge, or directly initiate a shock tube or length of detonating cord attached to the detonator. Examples of these types of DDT detonators, or other modified detonators, are described in, for example, U.S. Patent No. 2,400,103 (Cobb), U.S. Patent No. 3,096,714 (Yuill), U.S. Patent No.
20 4,727,808 (Wang et al.), U.S. Patent No. 4,316,412 (Dinegar and Kirkham), PCT Patent Publication No. WO97/22571 (Dumenko) published June 26, 1997, US Patent No. 5385098 (Lindquist et al.), and a related European application numbered as EP-A1-0365503 (Lindquist et al.).

In Dinegar (US 4,316,412) a detonator is described in which a bridgewire is
25 used to initiate a charge of potassium picrate and fine (10 micron) PETN pressed to a high density, in a burning mode. This reaction then progresses to a detonation reaction in an adjacent "transition charge" of fine PETN. The detonation of this transition charge effects detonation of the adjacent base charge. This device, however, is characterised by high confinement both to the
30 sides around the two charges and to the back around the bridgewire. Such high confinement in a standard commercial detonator is not possible due to the limited

dimensions of these detonators and is not desirable due to manufacturing difficulties.

In Wang (US 4,727,808), a fine secondary explosive (PETN < 20 micron and specific surface area of 5000-7000 cm²/g) is used as the initiating charge in order to allow a fast pressure build-up to cause the detonation of the adjacent transition charge of a lower density PETN. This detonation reaction causes the base charge of the detonator to detonate. This design, however, depends on a hot ignition source and strong back confinement provided by a small aperture in the confinement element to allow the fast pressure build-up. This detonator has a high degree of complexity in design, and is relatively expensive to manufacture.

Lindquist (US 5385098) describes a DDT detonator comprising a deflagration section having material in the form of a porous granulated material in order to provide a suitable reaction front. The granulated material is preferably a mixture of a secondary explosive and a combustion catalyst which have been granulated to form granules with a weight average particle size between 10 and 2000 microns; and made up of a plurality of primary crystals having a weight average particle size between 0.1 and 100 microns. The combustion catalyst is a material such as carbon, kryolites or compounds of aluminum, manganese, iron, cobalt, nickel, mercury, silver, zinc, lead, chromium, copper, and mixtures thereof.

While providing an improved DDT detonator, this device still requires strong confinement, and in particular, back-confinement of the initiating element which back confinement consists of a cup-shaped confinement shell (with an aperture), which surrounds the initiating element. Use of this cup-shaped confinement shell, together with the preferred use by Lindquist, of back-pressing of the initiating element, adds to the manufacturing cost and complexity of the completed detonator.

Thus, while DDT detonators have shown promise for the replacement of standard primary explosive-containing detonators, their reliability and ease-of-manufacture have led to continued interest in developing additional types of primary explosive-free detonators. In order to overcome these difficulties, other primary explosives-free detonators have been proposed; including devices such

as "flyer" plates (U.S. 3,978,791) or involve the use of lasers (U.S. 3,724,383). However, these have met with little commercial success due to operational and/or manufacturing difficulties.

A further alternative involves the use of high energy pyrotechnics, as
5 described in Canadian patent application No. 2215892.

However, it is still felt in the industry, that it would still be desirable to provide improved performance in a deflagration to detonation transition (DDT) detonator.

Accordingly, in light of the prior art, it would be desirable to provide a
10 composition for use in detonators which is preferably free from primary explosive, and which can be operated without requiring non-standard levels of confinement or the like.

Summary of the Invention

Accordingly, the present invention provides a detonator comprising:

- 15 (i) a hollow detonator shell having an open end and a closed end;
- (ii) an igniting device at the open end of said shell;
- (iii) optionally one or more delay elements adjacent said igniting device;
- (iv) an initiating element comprising an initiation portion and
20 optionally a transition portion; and
- (v) optionally a base charge,

characterized in that said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a
25 relatively small particle size, high-burn-rate, pressurizing initiator located within said interstitial spaces.

For the purposes of this application, the term "porous powdered explosive" refers to an explosive material which when loosely poured into a container, allows

air to pass through the material without a substantial amount of air resistance.

The term "powdered" is merely used to indicate that the material is not a liquid or a gas. Preferred materials useful as porous powdered explosives include materials such as pentaerythritoltetranitrate (PETN), cyclotrimethylenetrinitramine (RDX), cyclotetramethylenetetranitramine (HMX), trinitrophenylmethylnitramine (Tetryl), trinitrotoluene (TNT), or combinations thereof. Most preferably, however, the porous powdered explosive is PETN.

When used in the practise of the present invention, the relatively large particle size of the porous powdered explosive creates sufficient interstitial spaces to allow the high-burn-rate, pressurizing initiator to be located within the interstitial spaces even when the mixture is pressed to a desired density within the detonator. Thus, the term "porous" is used to describe a feature of a material to form significant amounts of interstitial spaces contained within the material. A preferred level of porosity is such that the porous, powdered explosive contains, when pressed into place, void spaces of up to 30%, by volume, and more preferably, between 15 and 30% by volume void space.

Further, the shape of the crystals of the porous powdered explosive can also influence the level of interstitial spaces, and thus influence its ultimate reaction properties. For example, a cylindrical configuration would typically allow for the void spaces to have a longer continuous volume when compared to a spherical configuration. Accordingly, cylindrical, prismatic, or generally non-spherical configurations are preferred to spherical or cubic configurations since the void space in the porous powdered explosive would be relatively larger for these configurations. Accordingly, it is preferred that the porous powdered explosive be cylindrical or prismatic in shape and have a crystal aspect ratio of length to width, of at least 3 to 1, and more preferably at least 4 to 1.

As previously stated, the porous powdered explosive is also relatively large when compared with the particle size of the high-burn-rate pressurising initiator. As a general guideline, it is preferred that the crystal particle size of the porous powdered explosive is greater than 10 times, on average, of the size of the high-burn-rate initiator. Further, it is preferred that the porous powdered explosive

-7-

has a number average particle size of between 100 and 500 microns, more preferably between 100 and 300 microns, and most preferably between 100 and 200 microns.

Unless otherwise specified, all particle sizes provided are based on number average particle sizes. Also, unless otherwise noted, all percentages are based on weight percentages.

It should be noted, however, that even with a number average particle size of greater than 100 microns, the porous, powdered explosive may contain particles which range from values below 100 microns. However, the number average size is still greater than 100. Further, the porous, powdered explosive may also contain a small portion of a fine powder having a smaller particle size. This fine powder can have, for example, a particle size of less than 20 microns, or less than 10 microns, or even less than 5 microns. Under some circumstances, however, this small amount of fine powder can assist in the fast ignition and rapid pressurization of the larger porous, powdered explosive particles, and thereby improve the efficiency of the transition from deflagration to detonation. The amount of this fine powder is preferably less than 10%, or more preferably, less than 5%, by weight of the porous, powdered explosive, and is not used to calculate the number average particle size of the porous powdered explosive.

The ultimate porosity of material utilized can be estimated and or adjusted for a given material by controlling the density of the material. For example, a typical sample of PETN has between 15 and 30% void space when tested at a density of 1.2 to 1.5 g/cc.

The term "high-burn-rate pressurising initiator" refers to a fast burning ignition compound or mixture, which has a fast ignition and which also generates an essentially continuous increase in burn rate as gas pressure increases. Preferably, the high-burn-rate initiator has a linear burn rate of greater than 1 cm/sec at a pressure of 2 atmospheres (when measured with a strand burning technique using cylindrical samples of 4 mm diameter or larger, pressed to more than 0.85 g/cc crystal density in a constant pressure bomb as described in Belyaev, A. F. et al. in "Transition from Deflagration to Detonation in Condensed

Phases", Israel Program for Scientific Translations, Jerusalem, 1975 and Svetlov, B. S. and Fogel'zang, A. E., "Combustion of fast burning explosives", Comb., Expl. and Shock Waves, Vol. 5, No. 1, 51, 1969).

More preferably, the burn rate of the high-burn-rate pressurising initiator
5 increases essentially continuously with pressure and reaches a value of greater than 2 cm/sec, and still more preferably, greater than 5 cm/sec, at a pressure of 50 atmospheres.

For example, pure potassium picrate has a linear burn rate of 1.5 cm/sec at 2 atmospheres. This burn rate increase to a maximum of 7 cm/sec at a pressure
10 of 7 to 8 atmospheres. The burn rate then decreases to a value of 2 cm/sec at a pressure of 70 atmospheres. This behaviour makes potassium picrate a candidate for only low pressure applications. However, for higher pressure applications, such as for use as part of an initiation portion of the present invention, this decrease in burn rate is not desirable since it reduces the rate of
15 pressurization of the detonator. When combined with potassium perchlorate, however, the decrease in burn rate is essentially eliminated and the burn rate increases essentially continuously with pressure. Accordingly, the combination of potassium picrate and potassium perchlorate provides a particularly effective mixture for use as the high-burn-rate pressurising initiator in the present
20 invention.

The high-burn-rate pressurising initiator also preferably provides a rapid increase in pressure so as to provide a shock wave suitable for initiation of the porous, powdered explosive. Generally, the high-burn-rate pressurising initiator will provide an increase in gas pressure equal to, or greater than 2 kbar, when
25 measured inside the confinement element which contains at least a part of the initiation portion. In practice, the pressure increase can be estimated from the amount of expansion of the confinement tube. More preferably, the increase in gas pressure will be greater than 5 kbar, and most preferably, will be greater than 10 kbar.

Materials which have a high burn rate, but which do not develop a significant gas pressure increase (in accordance with the values given above) are not preferred in the operation of the present invention.

- Preferred materials suitable for use in the high-burn-rate pressurising initiator include materials such as potassium picrate, potassium styphnate, lead styphnate, potassium trinitrobenzoate, or alkali or alkaline earth metal salts of nitro-aromatic compounds, and in particular, nitrophenols or nitrobenzoates, or mixtures thereof. More preferably, however, the high-burn-rate pressurising initiator is a mixture of a high burn rate explosive and an oxidizer. A more preferred composition for the high-burn-rate pressurising initiator is a mixture of a material having a high-burn-rate at low pressure, such as potassium picrate, potassium styphnate, lead styphnate, or potassium trinitrobenzoate together with an oxidizer such as potassium perchlorate or ammonium perchlorate. A preferred mixture of these materials comprises between 30 and 70% (by weight) oxidizer. More preferably, the mixture comprises between 30 and 70% potassium picrate and 30 to 70% potassium perchlorate. More preferably, the mixture comprises between 40 and 60% potassium picrate and potassium perchlorate. Most preferably, the mixture comprises about 50% potassium picrate and about 50% potassium perchlorate.
- With this preferred mixture, high burn rates are possible while also providing good levels of pressurization. This combination provides an improved ability to effect the transition from deflagration to detonation when combined with the PETN. This improved ability can be achieved with decreased levels of confinement and without the need for back-pressing. Thus, this preferred mixture provides clear advantages over the DDT formulations of the prior art.
- The materials used for the high-burn-rate pressurizing initiator preferably have a particle size small enough in at least one direction so that they can be located within the interstitial spacing in the porous powdered explosive. Accordingly, the components of the high-burn-rate pressurizing initiator preferably each have a particle size of less than 15 microns, more preferably less

-10-

than 10 microns, and even more preferably have a particle size of 5 microns or less.

In the present application, the term "intimate mixture" describes a combination of at least two materials which have been well mixed so that, in the particular mixture of interest in the present invention, the components of the high-burn-rate pressurising initiator is/are located within the interstitial spaces in the porous, powdered explosive(s).

The term "adjacent" when used in this specification means that two materials, such as the base charge and the initiating element, are located sufficiently close to one another that the reaction front passes from one material to the other. Contact between the materials is generally preferred, but is not required.

The initiation portion may contain other materials to modify its performance properties. Preferably, however, the initiation portion comprises at least 10% by weight of said intimate mixture of said porous, powdered explosive and said high-burn-rate pressurising initiator. More preferably, the initiation portion comprises at least 50%, and even more preferably, at least 90%, of said intimate mixture. Most preferably, however, the initiation portion comprises greater than 99% of said intimate mixture.

The ratio of porous powdered material to high-burn-rate pressurising initiator in the intimate mixture of the initiation portion of the initiating element is dependent on the materials selected, and the desired performance properties. However, preferably, the level of porous powdered material is at least 50% (by weight) of said intimate mixture, more preferably greater than 70% of said intimate mixture, and even still more preferably, is greater than or equal to 80% of said intimate mixture. Preferably, the minimum level of high-burn-rate pressurizing initiator is at least 5% of said intimate mixture.

In a most preferred embodiment, both components of the intimate mixture are not primary explosives and thus permit the production of a detonator which is free from primary explosives.

-11-

When present, the transition portion of the initiating element is located between the initiation portion and the base charge (also when present) or the closed end of the detonator. The transition portion is typically a secondary explosive which can be detonated by the reaction front passing through the initiation portion, and which can detonate with sufficient energy to detonate the adjacent base charge material. A preferred material for use as the transition portion is PETN having a particle size of between 75 and 185 microns, and which has a lower density than the base charge. Preferred densities for the initiation portion are between 1.0 and 1.2 g/cc.

In a further aspect, the present invention also provides a composition suitable for use in an explosive detonator which comprises an intimate mixture of a porous powdered explosive having interstitial spaces, and a high-burn-rate, pressurizing initiator located within said interstitial spaces.

In a still further aspect, the present invention also provides an initiating element comprising an initiation portion and optionally a transition portion characterized in that said initiation portion comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size, high-burn-rate, pressurizing initiator located within said interstitial spaces.

In a yet still further aspect, the present invention also provides a method of production of the detonators described. Further, the present invention also provides a method of blasting comprising initiating an explosive charge using a detonator, wherein the detonator is as described hereinabove with respect to the present invention.

Further objects and advantages of the present invention will be evident from the detailed description of the invention hereinbelow.

Brief Description of the Drawings

The invention may be more clearly understood by reference to the following detailed description of the invention, and the accompanying drawings wherein:

Figures 1 to 3 are cross-sectional drawings of in-hole detonators according to the present invention; and

Figures 4 to 6 are cross-sectional drawings of surface detonators according to the present invention.

Detailed Description of the Preferred Embodiments

The present invention is applicable to both in-hole and surface detonators.

Further, the detonators may be electronic, electric or non-electric. The term "detonator" is used in a general sense and is meant to include a variety of initiation devices which may also be referred to as blasting caps, initiators and the like.

The detonator may also be a "delay" detonator, by which term is meant that the detonator comprises means, such as a pyrotechnic delay element, a series of delay elements (e.g. a delay "train"), an electronic timing circuit, or some other device, to cause a time delay between initiation of the igniting device and the subsequent initiation of the initiation portion and/or base charge. However, the detonator may also be an instantaneous, non-delay detonator.

It should be noted that the materials used in the production of the delay element (or the delay "train") are typically not gas-generating, or produce very little gas during combustion. This is in distinct contrast to the high-burn-rate pressurising initiator used in the intimate mixture of the present invention.

It should also be noted that the intimate mixture may also include additional materials. However, all percentages values discussed herein are based on the weight ratios of the porous, powdered explosive and the high-burn-rate pressurising initiator, or are based on the total weight of just the initiation portion.

Other additional materials which may be included in the intimate mixture include materials such as explosives, pyrotechnics or propellants. Further, materials such as organic fuels, "inert" organic binders, and the like, which may or may not be consumed during the reaction/detonation may also be present.

- 5 However, preferably the levels of these additional materials is less than 25%, more preferably less than 10% and most preferably, less than 2% of the total weight of the porous, powdered explosive, the high-burn-rate pressurising initiator, and the additional material(s).

- 10 The additional material can include any suitable primary or secondary explosive or initiator which is added to modify the reaction characteristics of the initiation portion, but which does not meet the criteria of being either a porous, powdered explosive or a high-burn-rate pressurising explosive. This can include, for example, materials such as lead azide, or PETN of non-acceptable particle size (e.g. less than 100 microns). However, in light of the stated goal of
- 15 minimizing the use of a primary explosive, it is preferred that the initiation portion be essentially free of added primary explosives.

- A preferred additional material which may be used in combination with the initiation portion is a material which is a "molecular" explosive. Preferred molecular explosives are generally secondary explosive compounds wherein the
- 20 fuel and oxygen are present on the same molecule. Examples of preferred suitable secondary molecular explosives are non-acceptable particle sized PETN, RDX or HMX or mixtures thereof.

- The level of these materials should, however, be low enough so as to not interfere with the intimate mixing of the initiation portion, and thereby interfere
- 25 with the ability to locate the high-burn-rate pressuring initiator within the interstitial spaces of the porous, powdered explosive.

- Examples of other optional additional materials which may be incorporated into the initiation portion include fuels such as finely divided solids including sulphur or carbonaceous materials such as gilsonite, comminuted coke or
- 30 charcoal, carbon black, resin acids, sugars such as glucose or dextrose and other vegetable products such as starch, nut meal, grain meal and wood pulp; and

mixtures thereof. Also materials such as propellants and/or gas-generating compounds such as nitrocellulose or sodium azide based propellants, and the like, may be added. Further, binders (preferably energetic binders) such as polymeric materials (including nitrocellulose or GAP (glycidyl azide polymer) can also be included.

Additionally, or alternatively, the formulations of the present invention may be granulated in order to improve their flow properties and in order to reduce dusting. Granulation can be done by forcing a damp mixture through a certain screen size to form granules which are then dried. Granulation can also be done by adding a granulating agent. This agent is usually dissolved in a liquid and mixed with the energetic material(s). The damp mixture is also typically forced through a certain screen size to form granules which are then dried. In this case, the granulating agent acts as a binder to help hold the granules together. When granulated, the granules produced should have a particle size which is at least as large as the particle size of the crystals of the porous, powdered explosive. Accordingly, the present invention also includes detonators, and a production process, wherein all or part of the materials utilized have been subjected to a granulation process.

Granulating agents are well known within the explosives industry. One suitable granulating agent for the formulations described herein is a hydroxypropyl methylcellulose material sold under the trade mark Methocel K4MS (available from Dow Chemical).

The amount of initiation portion present in the initiating element of the detonators of the present invention can vary widely depending on its composition, detonator design, and desired output. These parameters have been previously discussed. For typical situations in a standard sleeve having a 3.8 mm inside diameter (ID), the level of initiation portion is preferably between 10 and 200 mg, more preferably between 50 and 150 mg, and most preferably between 100 and 150 mg.

The amount of transition portion present in the initiating element can also vary widely depending on composition, design and desired output. The transition

portion can also be eliminated under some circumstances. Accordingly, the level of transition portion can, for example, vary from 0 to 200 mg, but more preferably is between 50 and 150 mg. Most preferably the level of transition portion is between 100 and 130 mg.

5 The initiation portion and the transition portion (when present) together form the initiating element. Using the initiating element of the present invention, less confinement of the initiating element is required. Accordingly, the confinement may consist of a simple metal sleeve which is adapted to be fitted within a standard detonator shell. The confinement sleeve is preferably a copper, steel or
10 stainless steel sleeve which is sized so as to closely fit within the shell of a standard detonator. For example, in a standard detonator having an inside diameter (ID) of 6.8 mm, the confinement sleeve will preferably have an outside diameter (OD) of 6.3 mm and a wall thickness of between, for example, 0.1 to 1.5 mm. However, the inner diameter of the confinement sleeve can vary depending
15 on the amount of confinement desired. Most preferably, the confinement sleeve has a wall thickness of about 1.25 mm and is made of steel because of its high strength to mass ratio.

With the formulations of the present invention, it should be noted that the requirement for back-confinement is eliminated, and that there is no need for a
20 cup-shaped confinement means with small apertures. Accordingly, the detonators of the present invention have manufacturing advantages over the prior art DDT detonators.

Under some configurations, it is also possible to eliminate the need for complete confinement of all of the initiating element. Generally, however, it is
25 typically preferable to provide confinement at at least the interface where the initiation portion is first initiated. This aids in ensuring that the DDT reaction has sufficient confinement to transfer from deflagration to detonation within an acceptably short length of the initiation portion and thereby is able to effect detonation of the transition portion or the base charge.

Preferably, all materials used in the production of the intimate mixture of the initiation portion, or more generally, all materials used in the production of the detonators of the present invention, are powdered materials at 20 ° C.

Detonators of the present invention are primarily used in in-hole applications. However, as previously stated, detonators of the present invention may be used in surface applications. These surface detonators typically contain a smaller base charge or omit the base charge. Alternatively, the base charge may be a reduced energy base charge comprising, for example, PETN together with an inert salt.

When present, the base charge may be any of the materials described hereinabove with respect to prior art detonators. However, preferably the base charge used in the detonators of the present invention is a secondary explosive, and more preferably is a molecular secondary explosive. The amount of base charge present will also vary depending on the desired features of the detonator. However, typical levels for the base charge in an in-hole detonator will range from 100 to 900 mg, and more preferably will be between 200 and 800 mg. Surface detonators will typically contain less of a base charge or a less energetic base charge.

Further, in a surface detonator, the density and length of the initiation portion can be tailored to achieve a low order detonation (i.e. does not achieve full detonation) which does not fragment the confinement sleeve. This design has the advantage that a low order detonation can be used to initiate adjacent shock tubes while reducing the risk of damage resulting from the fragments created caused by a high order detonation. In this embodiment of a surface detonator, the transition charge and/or the base charge can be omitted.

Alternatively, the base charge can be diluted (by an essentially inert substance) or a low density base charge can be used in order to produce a lower pressure detonation which is more suitable for initiation of shock tube. The lower pressure also reduces fragments and therefore, reduces the damages which might be caused by high density, and thus, high pressure base charges.

With the exception of the DDT element, in general, and the composition of the initiating element, in particular, production of the detonators of the present invention is essentially identical to prior art techniques. These techniques for production are well known to those skilled in the art. Using known techniques, all or a portion of the initiating element components may be added to the detonator shell with the confinement sleeve, and pressed to the desired density.

Alternatively, all or a portion of the initiating element components may first be pressed into the confinement sleeve prior to inserting the sleeve into the detonator shell.

The addition of a delay element to provide a delay detonator should have little or no impact on the operation of the detonators of the present invention, and manufacture of the delay element is a standard technique in the explosive detonator technology.

The detonator igniting device can be any suitable device which will initiate the delay element and/or directly initiate the initiation portion. Suitable igniting devices include electric "matches", bridge wires, shock tube, safety fuse, detonating cord, or the like, which are inserted into the open end of the detonator shell and which are capable of generating a flame and/or shock wave. Other devices which may be included as igniting devices in the detonators of the present invention include electronic detonator "hotspots", "slapper" detonators, lasers which are capable of generating an energy pulse through, for example, a fibre optic cable, and the like.

As previously discussed, a benefit of using the formulations of the present invention is that the initiating element is able to make the transition from deflagration to detonation in a standard thin wall detonator with limited levels of confinement, and do not require additional heavy confinement means, such as heavy walled steel or copper sleeves and the like. Use of these simpler confinement means is preferable to the confinement means described in the DDT prior art. This improvement provides manufacturing advantages since the design of the detonator may be essentially the same as for prior art detonators. The only significant difference is the replacement of the primary explosive by a simple

cylindrical DDT initiating element which can be manufactured using processes similar to known processes such as, the processes used to produce rigid technology delay elements.

A preferred formulation for the initiation portion of the initiating element, according to the present invention, for use in both surface or in-hole detonators comprises a mixture of 5 to 15% potassium picrate, 5 to 15% potassium perchlorate and 70 to 90% PETN. In this embodiment, the preferred particle size of the materials is as follows: (i) potassium picrate - between 0.5 and 3 microns; (ii) potassium perchlorate - between 1 and 10 microns; and (iii) PETN - between 80 and 120 microns.

It may also be necessary, as is common in this art, to adjust the density of the initiation portion by pressing the mixture during production. Preferably, the density of the initiation portion after pressing is between 1.2 and 1.5 g/cc. However, this may vary depending on the materials selected for production of the initiation portion and may vary depending on the level of confinement selected.

A preferred formulation for the transition portion of the initiating element is the use of PETN having a particle size of between 75 and 180 microns, with a number average particle size of at least 100 microns, and pressing to a density of 1.0 to 1.2 g/cc.

This combined initiating element formulation has demonstrated the ability to produce detonators having properties which are generally equivalent to prior art detonators containing primary explosives. However, a feature of the initiating element of the present invention is that the energy output and VOD, as well as other properties such as sensitivity, heat stability, and the like may be adjusted or modified by changes to the initiating element formulations.

Preferably, the initiating element is formulated to provide acceptable performance standards over a wide temperature range from at least -40 ° C to greater than 120 ° C. Also, it is preferred that the initiating element be formulated so as to be of roughly equivalent length to the initiation portions of prior art detonators. This may be, for example, a length of about 15 to 18 mm but this can vary depending on the detonator design. This permits the detonators produced in

accordance with the present invention to be of similar length and size to prior art detonators.

One significant feature of the detonators of the present invention is that all materials used for production can be non-primary explosives. Accordingly, the detonators produced may be handled without the precautions necessary for handling primary explosives. Also, because of the low level or absence of primary explosive in the detonators in the preferred embodiments of the present invention, the detonators produced show improved impact resistance and improved propagation resistance over conventional detonators. Impact resistance is a measurement to determine whether a detonator will cause initiation of an outgoing shock tube or detonating cord when the detonator is subjected to the impact of a steel weight dropped from a measured height. For the purposes of this specification, the steel weight is 25 pounds (11.4 kg). Standard detonators of the prior art typically initiate the shock tube or the detonating cord when the steel weight is dropped from a height of 7 feet (2.15 metres) or less for surface detonators, or 4 feet (1.2 metres) or less for in-hole detonators. Accordingly, an impact resistant detonator for the purposes of this specification is one which does not initiate shock tube or detonating cord when the steel weight is dropped from a height of 15 feet (2.3 metres) for a surface detonator and 10 feet (3.1 metres) for an in-hole detonator.

Accordingly, the present invention provides detonators which are impact resistant, according to the definition herein provided, and also provides a process for the production of detonators which are impact resistant.

In a similar manner, the detonators of the present invention have improved resistance to propagation. This property is defined as the ability to resist detonation by a detonator caused by the detonation of an adjacent detonator.

Accordingly, the present invention also provides a surface or in-hole detonator, and a process for producing a detonator, which is propagation resistant. Currently, the formulations and design of the present invention facilitates the development of detonators and low cost packaging which complies with current UN standard 1.4B packaging classification requirements.

With respect to the drawings, it should be noted that a major advantage of the detonators of the present invention is that they can be produced in a fashion similar to existing prior art detonators. Accordingly, the detonators are similar in appearance to prior art detonators with the exception that the traditional, prior art, initiation portions have been replaced by the compositions described in the present invention.

In Figure 1 a non-electric, in-hole delay detonator is shown wherein 1 designates a metal tubular shell with an inside diameter of 6.7 mm, and closed at its bottom end. Within shell 1 is a base charge 2 of 800 mg of PETN (greater than 200 micron particle size) pressed to a density of 1.5 g/cc. Adjacent the base charge 2 is initiating element 3 which consists of a transition portion 4 and an initiation portion 5. Initiation portion 5 is held within confinement sleeve 8 and is an intimate mixture of 10% potassium picrate (2 to 20 micron particle size), 10% potassium perchlorate (3 micron particle size) and 80% PETN (75 to 180 micron particle size) which mixture has been dry mixed and pressed to a density of 1.5 g/cc. Transition portion 4 is also held within confinement sleeve 8 and consists of PETN (75 to 180 micron particle size) which has been pressed to a density of 1.1 g/cc. Sleeve 8 is a cylindrical steel sleeve which has an outside diameter of 6.3 mm and an inside diameter of 3.8 mm.

A delay train of a mixture of red lead, silicon and barium sulphate is shown at 15 and is contained within a metal tube 16. Above delay train 15 is the open end of an inserted shock tube 10 which rests against an anti-static cup 11. Shock tube 10 is held centrally and securely in tube 1 by means of closure plug 12 and crimp 13. When shock tube 10 is initiated at its remote end (not shown) a reaction front passes along the tube, through anti-static cup 11 and ignites delay charge 15. Delay charge 15 burns down to initiation portion 5 at a controlled rate so as to provide the desired delay time. Initiation portion 5 subsequently effects initiation of transition element 4. As the reaction front passes through initiating element 3, a DDT reaction occurs so that initiating element 3 goes through a deflagration to detonation transition. Accordingly, a portion of initiating element 3

eventually detonates. This detonation of initiating element 3 subsequently causes the detonation of base charge 2.

In Figure 2, an electric delay detonator is shown which is similar to the non-electric detonator of Figure 1. In this embodiment, however, the shock tube assembly is replaced with electric match head 26 which is connected to a pair of electrically conducting leads 27. Leads 27 pass through a rubber insert 28 which insert is crimped into place by a crimp 29 in shell 1. Otherwise, all other features are identical to the embodiment described in Figure 1. In Figure 2, and all other subsequent figures, like numerals are used to represent equivalent features.

In operation, an electrical signal passes through leads 27 and causes match head 26 to initiate. The initiation of match head 26 causes delay train 15 to begin burning at its upper end as in the detonator of Figure 1. From this point, operation of this detonator is identical to the detonator of Figure 1.

In Figure 3 a non-electric, instantaneous detonator is shown which is identical to the detonator described in Figure 1 with the exception that delay element 15 and metal tube 16, have been removed so that the reaction front from shock tube 10 directly initiates initiation portion 5. Again, from this point, operation of this detonator is identical to the detonator of Figure 1.

In Figure 4, a non-electric delay surface detonator is shown which is essentially identical to the detonator of Figure 1. However, in this surface detonator, base charge 2 of Figure 1 has been replaced with a lower output base charge 2A consisting of 200 mg of a mixture of 70% by weight PETN and 30% talc.

In Figure 5, an electric surface detonator is shown which is similar to Figure 2. However, base charge 2 has been removed. Detonation of initiating element 3 is utilized to provide initiation of any shock tubes (not shown) which are adjacent to detonator 1.

In Figure 6, a non-electric surface detonator is shown which is similar to the detonator shown in Figure 4 with the exception that base charge 2A and transition portion 4 has been removed. In this embodiment, a larger portion of initiation portion 5 is used alone and undergoes the DDT reaction. The resulting

detonation is utilized to provide initiation of any shock tubes (not shown) which are adjacent to detonator 1.

Numerous variations and modifications of these devices are commonly known within the industry. For example, shock tubes or electric match heads can be replaced by a variety of devices which can effect initiation of the delay train, or instantaneous initiation of the initiation portion in a non-delay detonator. Further, the initiation portion can be directly initiated by a suitable device in an electronic detonator which eliminates the delay train in a delay detonator.

The utility of the invention will now be described, by way of example only, by reference to the following examples.

Examples

A series of detonators (both surface and in-hole types) were prepared using formulations according to the present invention. The detonators were tested for suitability for use. The detonator design and results were as follows:

15 Surface Detonators

Example 1

140 mg of an initiation portion consisting of a mixture of 10 parts of potassium picrate and 90 parts of PETN was poured into a cylindrical steel element 18 mm long, 6.3 mm OD, 3.8 mm id and pressed at 1.5 g/cc density. The remaining space in the element was filled with 100 micron PETN (as a transition portion) and was pressed to a density of 1.1 g/cc. An adhesive paper retaining cover was applied and the element inverted and loaded onto 50 mg of PETN (as a base charge) contained in a 6.7 mm ID detonator shell. A 75 ms delay was placed on top of the steel element and a lead sealer element was crimped on top. The

detonator was placed in a connector block with 3 shock tubes ahead of the base charge and one to each side. When the detonator was fired using a line of shock tube all the tubes were initiated at both 20° and - 40° C. The shrapnel produced was less than from a conventional surface detonator containing 300 mg of lead
5 azide.

Example 2

The base charge in Example 1 was replaced by 200 mg of a mixture of 70 parts of PETN and 30 parts of talc. The talc was present to dilute the output of the base charge by reducing its detonation velocity and reduce shrapnel production. When
10 fired 5 shock tubes arranged as in Example 1 were initiated and the shrapnel production was less than from a conventional surface detonator.

Example 3

The base charge in Example 1 was removed . When fired up to 6 tubes arranged in a 3 by 2 arrangement ahead of the detonator could be initiated as could 5
15 tubes arranged as in Example 1 at 20° C. At -40° C, 4 out of 5 tubes were initiated in the latter configuration. The detonator also gave less shrapnel output than a conventional surface detonator.

Example 4

The initiating element from the detonator in Example 3 was filled only with the
20 initiation portion and all other aspects of the detonator remaining the same. When fired it was able to initiate up to 6 shock tubes arranged in a 3 by 2 pattern and produced minimal shrapnel.

Example 5

Steel confinement elements, 18 mm length 6.3 mm OD 3.8 mm ID, were filled with
25 315 mg of the initiation mixture of Example 1 and pressed to 1.4 to 1.5 g/cc density. The element was loaded into a detonator shell containing a mixture of 10% 60 micron potassium picrate and 90% 75-180 micron PETN confined in an

-24-

inverted brass cup, with a hole in its bottom. The delays were loaded on top of the steel element. The brass cups had an OD of 6.40 mm, an ID of 5.73 mm and the diameter of the hole in its bottom was 2.44 mm. The detonators were tested in the 5 shock tube configuration described in Example 1. The number of shock tubes initiated for the different configurations are shown in the Table 1. The steel elements did not shatter and produced no shrapnel.

Table 1: Number of shock tubes (out of 5) initiated for different deflagrative element length and base charge configurations

Base Charge Vol.	Base charge density	Ignition Charge Length mm				
		18	14.5		10	
cc	g/cc	20° C	20° C	-36° C	20° C	-36° C
0.24	1.35	2				
	1.1	4				
	1	5				
	0.9	5, 5	5			
	0.45		5	5	5	5
0.14	0.9		5		0	

In-Hole Detonators

5 Example 6

140 mg of a mixture of 75-180 micron PETN (80% by mass), 2-20 micron potassium picrate (10%) and 3 micron potassium perchlorate (10%) was poured into a 18 mm length 6.3 mm OD, 3.8 mm ID stainless steel tube and pressed to a density of 1.5 g/cc. The remaining space of the tube (the transition portion) was

10 filled with 130 mg of 75 - 180 micron PETN and pressed to a density of 1.1 g/cc. The initiating element form was inserted into a 6.5 mm ID aluminum detonator shell containing 0.8 g PETN base charge pressed to 1.5 g/cc density. Pyrotechnic delay elements were placed on top of the initiating element followed by a shock tube. Four detonators were tested on aluminum witness blocks and

15 all four detonators produced dents of more than 2 mm depth.

Example 7

Three charge weights of 100, 120 and 140 mg of the same initiation mixture as in Example 6 were pressed to densities of 1.2, 1.3, 1.4 and 1.5 g/cc in stainless steel tubes (6.3 mm OD and 3.8 mm ID) of lengths varying from 15.5 to 18 mm.

- 5 These produced initiation portions of various lengths depending on the mass and density combination. The transition portion was kept at a constant length of 10 mm by filling in the remaining space of the confinement tube with 130 mg of 75 - 180 micron PETN and pressing to a density of 1.1 g/cc. The initiating elements were tested in the same configuration as Example 6 except that the base charge
- 10 was made of an inert material, sodium chloride, pressed to a density of 1.7 g/cc, which closely simulates the dynamic response of PETN at 1.5 g/cc. All initiating elements except one shattered. The only intact piece was from the 100 mg initiation portion with a 1.4 g/cc density which was expanded to 8.9 mm. It is believed that this resulting pressure was more than enough to cause the base
- 15 charge to fully detonate. These tests show that an initiation portion with mass above 100 mg in density range of 1.2 to 1.5 g/cc and the 10 mm column length of transition charge can cause the base charge to detonate.

Example 8

- Two electric detonators were made as described in respect of Figure 2. On
- 20 initiation, both detonators produced dents in the aluminum witness block of more than 2 mm.

Example 9

- 140 mg of an initiation portion consisting of potassium picrate (10%) and PETN (90%), as used in Example 6, was used as the initiation portion in Example 6.
- 25 detonators were made using procedure as Example 6 and when they were fired on aluminum witness blocks. All produced dents of more than 2 mm.

-27-

Example 10

244 mg of the initiation portion as in Example 6 was loaded into 18 mm long steel tubes of 6.3 mm OD 5.07 mm ID at a density of 1.4 g/cc and the remaining space was filled with a transition portion of PETN pressed to 1.1 g/cc. Two detonators were made as in Example 6 using these thin walled steel DDT elements. When fired, the two detonators produced dents of more than 2 mm deep in the aluminum witness blocks.

Example 11

225 mg of the initiation portion as in Example 6 was loaded into 18 mm long copper tubes of 6.3 mm OD 5.16 mm ID at a density of 1.35 g/cc and the remaining space was filled with a transition portion of PETN pressed to 1.1 g/cc. Two detonators were made as in Example 6 using these thin walled copper tubes. When the shock tubes were fired, the two detonators produced dents of more than 2 mm deep in the aluminum witness blocks.

Example 12

A test was carried out to evaluate the effect of back venting, which simulates a potential application problems for DDT detonators. These problems are commonly encountered in field application situations and could be caused, for example, by physical distortion of the detonator shell by transmitted shock from adjacent boreholes or misalignment of the delay elements in the manufacture process. Two detonators were prepared as in Example 6 with the addition of a 1.54 mm thick washer (6.4 mm OD and 3.4 mm ID) between the delay element and the initiating element. A venting hole was created in the washer by cutting a 1.25 mm slot radially on the washer and the corresponding location of the aluminum detonator shell was also cut to allow venting. When the shock tubes were fired, both detonators fully detonated producing dents of more than 2 mm on the aluminum blocks.

Example 13.

Example 12 was repeated with the initiation mixture of Example 9. Two detonators were made and they did not produce any dents on the aluminum and the OD of the stainless steel tube expanded to only 6.39 mm.

5 Example 14

170 mg of a dry mix of 2-20 micron potassium picrate (10% w/w) and 90-425 micron PETN (90% w/w) was poured into a 28 mm length, 6.3 mm OD, 3.3 mm ID zinc element and pressed at 4.6 kPa. The space in the element was filled with 100 micron (approximate size) recrystallised PETN fraction prepared by
10 controlled crystallization from acetone/water. This charge was pressed at 1.2 kPa. The space left in the element was filled with loose 100 micron PETN and an adhesive paper circle placed over the end of the zinc element. The zinc element was inverted and loaded into a 6.7 mm ID aluminum detonator shell containing a 0.8 g PETN base charge pressed at 5.8 kPa. When initiated by a shock tube,
15 out of 10 detonators fired as indicated by witness plates and by damage to the zinc elements.

Example 15

The potassium picrate in Example 14 was replaced by 3-20 micron potassium styphnate. Five out of 5 detonators fired successfully.

20 Example 16

The potassium picrate in Example 14 was replaced by 10-30 micron potassium trinitrobenzoate. Five out of 5 detonators fired successfully.

Example 17

120 mg of a mix of ultra fine PETN (granular shaped particle with average 2
25 micron particle size, surface area ~6800 cm²/g) (80% by mass), 2-20 micron potassium picrat (10%) and 3 micron potassium perchlorate (10%) was poured into a 18 mm length 6.3 mm OD, 3.8 mm ID stainless steel sleeve and pressed to

a density of 1.3 g/cc. The remaining space of the tube (the transition portion) was filled with 150 mg of inert sodium chloride and pressed to a density of 1.3 g/cc. The initiating element was inserted into a 6.5 mm ID aluminum detonator shell containing 0.8 g sodium chloride inert base charge pressed to 1.7 g/cc density.

- 5 Pyrotechnic delay elements were placed on top of the initiating element followed by a shock tube. Three detonators were fired and the average diameter of the expanded steel sleeves was 6.46 mm and the corresponding maximum transient pressure was estimated to be about 3 kbar. The tests were repeated with three other detonators prepared using a larger size PETN (spheroidal shaped with
- 10 average particle size of 160 microns, surface area $\sim 210 \text{ cm}^2/\text{g}$). These three detonators were fired and the average diameter of the expanded steel sleeves was 6.71 mm, the corresponding maximum transient pressure was estimated to be about 6.5 kbar. These experiments demonstrate the utility of the larger PETN particle size in the present invention.

15 Example 18

- To illustrate the effect of particle geometry on the effectiveness of the present invention, two types of PETN particles were used. One type had a spherical shape with an aspect ratio of about one and the other had an elongated prismatic shape with an average aspect ratio of about 4. The diameter range of both were
- 20 75 to 180 microns. Example 17 was repeated with two initiation portions using these two types of PETN. 175 mg of these initiation portions were poured into 20 mm length, 6.3 mm OD, 3.8 mm ID stainless steel sleeves and pressed to a density of 1.4 g/cc. The remaining space of the tube (the transition portion) was filled with 150 mg of inert sodium chloride and pressed to a density of 1.3 g/cc.
- 25 These elements were prepared and fired as in Example 12. The average expanded element diameters were found to be 7.55 and 7.1 mm for the particles with aspect ratios of 4 and 1 respectively. The corresponding estimated pressures were 15 and 11 kbar respectively.

Example 19

For comparison, Example 14 was repeated but with a transition portion consisting of PETN (specific surface area of 3300 cm²/g) at a density of 1.6 g/cc as described by Dinegar in US patent No. 4316412. Because of the high density, this charge was pressed first. 170 mg of the potassium picrate-PETN composition of Example 14 was pressed on top and the resulting "initiating element" was loaded into a shell. When initiated by a shock tube, the "initiating element" deflagrated and split the confinement sleeve without fragmenting it. The base charge was not initiated.

Similar results were obtained when PETN with a specific surface area of 3300 cm²/g was used in both the initiation portion and transition portion. These combinations are therefore, not suited to lower confinement conditions as exemplified in the present invention.

Having described specific embodiments of the present invention, it will be understood that modifications thereof may be suggested to those skilled in the art, and it is intended to cover all such modifications as fall within the scope of the appended claims. Additionally, for clarity and unless otherwise stated, the word "comprise" and variations of the word such as "comprising" and "comprises", when used in the description and claims of the present specification, is not intended to exclude other additives, components, integers or steps.

CLAIMS:

1. A detonator comprising:
- (i) a hollow detonator shell having an open end and a closed end;
 - 5 (ii) an igniting device at the open end of said shell;
 - (iii) optionally one or more delay elements adjacent said igniting device;
 - (iv) an initiating element comprising an initiation portion and optionally a transition portion; and
 - 10 (v) optionally a base charge,

characterized in that said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size, high-burn-rate, pressurizing initiator located within
15 said interstitial spaces.

2. A detonator as claimed in Claim 1 wherein said porous powdered explosive is PETN, RDX, HMX, Teteryl, TNT or a mixture thereof.

3. A detonator as claimed in Claim 2 wherein said porous powdered explosive is PETN.

20 4. A detonator as claimed in Claim 3 wherein said PETN has a number average particle size of greater than 100 microns.

5. A detonator as claimed in Claim 1 wherein said high burn rate explosive is potassium picrate, potassium styphnate, lead styphnate, potassium trinitrobenzoate, or alkali or alkaline earth metal salts of nitro-aromatic
25 compounds, or mixtures thereof.

6. A detonator as claimed in Claim 5 wherein said high burn rate explosive is potassium picrate.

7. A detonator as claimed in Claim 1 wherein said high-burn-rate, pressurising initiator is a mixture of two separate components, namely a high burn
5 rate explosive and an oxidizer.

8. A detonator as claimed in Claim 7 wherein said oxidizer is potassium or ammonium perchlorate.

9. A detonator as claimed in Claim 8 wherein said oxidizer is potassium perchlorate.

10 10. A detonator as claimed in Claim 1 wherein said initiation portion comprises between 5 and 15 %, by weight of said oxidizer, and between 5 and 15% of said high burn rate explosive, which together form said pressurizing initiator, and 70 to 90% of said porous powdered explosive.

11. A detonator as claimed in Claim 1 wherein said transition portion is
15 PETN, RDX, HMX, Tetryl or mixtures thereof.

12. A detonator as claimed in Claim 11 wherein said transition portion is PETN.

13. A detonator as claimed in Claim 12 wherein said PETN is pressed to a density of between 1.0 and 1.2 g/cc.

20 14. A detonator as claimed in Claim 1 wherein said confinement sleeve is a steel, copper or stainless steel sleeve.

-33-

15. A detonator as claimed in Claim 14 wherein said confinement sleeve is a circular sleeve having a wall thickness of between 0.1 and 1.5 mm.

16. A detonator as claimed in Claim 1 wherein said initiation portion comprises a mixture of 5 to 15% by weight potassium picrate having a number
5 average particle size of less than 10 microns, 5 to 15% potassium perchlorate having a particle size of less than 10 microns, and 70 to 90% PETN having a particle size of greater than 100 microns, and wherein said initiation portion has been pressed into a confinement sleeve so as to have a density of between 1.2 and 1.5 g/cc.

10 17. A detonator as claimed in Claim 16 wherein said transition portion comprises PETN having a particle size of greater than 100 microns and has been pressed into a confinement sleeve so as to have a density of between 1.0 and 1.2 g/cc.

15 18. A detonator as claimed in Claim 1 wherein said initiation portion comprises additional components selected from the group consisting of explosives, propellants, organic fuels, or binders or combinations thereof.

19. A detonator as claimed in Claim 1 wherein said igniting device is a flame and/or shock wave from an electric match, a bridge wire, a shock tube, or a detonating cord which is inserted into the open end of the detonator shell.

20 20. A detonator as claimed in Claim 1 wherein said detonator is an electronic detonator.

21. A detonator as claimed in Claim 1 which is essentially free of added primary explosives.

22. A detonator as claimed in Claim 1 comprising a delay element adjacent said igniting device, so as to form a delay detonator.

23. A detonator as claimed in Claim 1 wherein said detonator is impact resistant.

5 24. A detonator as claimed in Claim 1 wherein said detonator is propagation resistant.

25. An in-hole detonator comprising:

- (i) a hollow detonator shell having an open end and a closed end;
 - (ii) an igniting device at the open end of said shell;
 - 10 (iii) optionally a delay element adjacent said initiating charge;
 - (iv) an initiating element comprising an initiation portion adjacent said delay element or said igniting device, and optionally a transition portion; and
 - (v) a base charge,
- 15 characterized in that said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size, high-burn-rate, pressurizing initiator located within said interstitial spaces.

- 20 26. A surface detonator comprising
- (i) a hollow detonator shell having an open end and a closed end;
 - (ii) an igniting device at the open end of said shell;
 - (iii) optionally a delay element adjacent said initiating charge; and
 - (iv) an initiating element comprising an initiation portion adjacent said
- 25 delay element or said igniting device, and optionally a transition portion;

-35-

characterized in that said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size, high-burn-rate, pressurizing initiator located within
5 said interstitial spaces.

27. A surface detonator comprising

- (i) a hollow detonator shell having an open end and a closed end;
- (ii) an igniting device at the open end of said shell;
- (iii) optionally a delay element adjacent said initiating charge; and
- 10 (iv) an initiating element comprising an initiation portion adjacent said delay element or said igniting device,

characterized in that said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a
15 relatively small particle size, high-burn-rate, pressurizing initiator located within said interstitial spaces, and wherein said initiation portion achieves only a low order detonation.

28. A surface detonator as claimed in Claim 26 or 27 wherein said detonator additionally comprises a base charge, and wherein the shock wave
20 produced by said base charge is reduced by using a diluted base charge, or a low density base charge.

29. An initiating element for use in a detonator comprising an initiation portion and optionally a transition portion wherein said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture
25 of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size, high-burn-rate, pressurizing initiator located within said interstitial spaces.

-36-

30. A process for manufacturing a detonator as claimed in Claim 1 comprising, in order,:

- (i) optionally inserting a base charge into a detonator shell;
- (ii) inserting an initiating element comprising an initiation portion and
5 optionally, a transition portion, into said detonator shell;
- (iii) optionally inserting a delay element into said detonator shell; and
- (iv) inserting an igniting device into said detonator shell;

wherein all components are operationally adjacent each other, and wherein said initiation portion comprises an intimate mixture of a relatively large particle size,
10 porous powdered explosive having interstitial spaces, and a relatively small particle size, high-burn-rate, pressurizing initiator located within said interstitial spaces.

31. A process as claimed in Claim 30 additionally comprising the step of granulating the initiation portion.

15 32. A process as claimed in Claim 31 wherein said initiation portion is combined with a granulating agent prior to granulation.

33. A method of blasting comprising initiation of an explosive charge utilizing at least one detonator, wherein at least one detonator is as claimed in Claim 1.




Fig. 1




Fig. 2




Fig. 3






Fig. 4

3/3

**Fig. 5****Fig. 6**

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU 99/00940

A. CLASSIFICATION OF SUBJECT MATTERInt Cl⁶: F42B 3/195, 3/12, 3/14, 3/16; C06C 7/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC F42B 3/10, 3/195, 3/12, 3/14, 3/16; C06C 7/00, 7/02

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

AU IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPAT with keywords

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4156390 A (FERGUSON et al) 29 May 1979 Column 4, lines 8-19	1-3, 5-9, 11-12, 14-15, 18-21, 23-27, 29-30, 33
Y	Column 4, lines 8-19	1-33
Y	AU 73573/98 A (THE ENSIGN-BICKFORD COMPANY) 30 October 1998 Whole document	1-33

☐ Further documents are listed in the
continuation of Box C

☒ See patent family annex

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search
17 November 1999

Date of mailing of the international search report
24 DEC 1999

Name and mailing address of the ISA/AU
AUSTRALIAN PATENT OFFICE
PO BOX 200
WODEN ACT 2606
AUSTRALIA
Facsimile No.: (02) 6285 3929

Authorized officer

JEFFREY CARL
Telephone No.: (02) 6283 2543

INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU 99/00940

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member			
AU	73573/98	WO	98/45663	US	5889228	ZA	9802987
<p>END OF ANNEX</p>							

- 1 -

Non-primary DetonatorsField of the Invention

5 The present invention relates to explosive detonators comprising compositions which are characterized by being essentially free from molecular primary explosives, to compositions suitable for use in detonators, and to the manufacture of detonators.. The invention further relates to initiating elements for use in detonators and to a method of blasting.

10

Description of the Related Art

Detonators, including electronic, electric and non-electric types, are widely employed in mining, quarrying and other blasting operations. In-hole detonators
15 are generally used to initiate an explosive charge which has been placed in a borehole, while surface detonators are generally used outside of the borehole to initiate one or more explosive initiating signal means such as shock tube or detonating cord.

Modern commercial detonators typically comprise, in the case of an in-hole
20 detonator, a metallic shell which is closed at one end and which contains, in sequence from the closed end, a base charge of a detonating, secondary explosive, such as for example, pentaerythritoltetranitrate (PETN), and a primer charge of a heat-sensitive, detonable, primary explosive, such as for example, lead azide, which is above and adjacent to the base charge. In a delay detonator,

AMENDED SHEET
IPE/AU

- 1A -

adjacent the primary explosive is an amount of a deflagrating or burning composition of sufficient quantity to provide a desired delay time. Above the delay composition (if present) is an electric match, a low energy detonating cord or shock wave conductor (such as shock tube), or the like, retained in the open end
5 of the metallic shock.

Surface detonators are generally identical to in-hole detonators with the exception that the base charge of high explosive is preferably reduced or omitted to give lower output. The output is preferably reduced to a level sufficient to initiate adjacent shock tube, detonating cord and the like, without, for example,

~~5~~

as "flyer" plates (U.S. 3,978,791) or involve the use of lasers (U.S. 3,724,383). However, these have met with little commercial success due to operational and/or manufacturing difficulties.

5 A further alternative involves the use of high energy pyrotechnics, as described in Canadian patent application No. 2215892.

However, it is still felt in the industry, that it would still be desirable to provide improved performance in a deflagration to detonation transition (DDT) detonator.

10 Accordingly, in light of the prior art, it would be desirable to provide a composition for use in detonators which is preferably free from primary explosive, and which can be operated without requiring non-standard levels of confinement or the like.

Summary of the Invention

Accordingly, the present invention provides a detonator comprising:

- 15 (i) a hollow detonator shell having an open end and a closed end;
(ii) an igniting device at the open end of said shell;
(iii) optionally a delay element adjacent said igniting device;
(iv) an initiating element comprising an initiation portion and
20 optionally a transition portion; and
(v) optionally a base charge,

characterized in that said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a
25 relatively small particle size, high-burn-rate pressurizing initiator located within said interstitial spaces.

For the purposes of this application, the term "porous powdered explosive" refers to an explosive material which when loosely poured into a container, allows

air to pass through the material without a substantial amount of air resistance.

The term "powdered" is merely used to indicate that the material is not a liquid or a gas. Preferred materials useful as porous powdered explosives include materials such as pentaerythritoltetranitrate (PETN), cyclotrimethylenetrinitramine (RDX), cyclotetramethylenetetranitramine (HMX), trinitrophenylmethylnitramine (Tetryl), trinitrotoluene (TNT), or combinations thereof. Most preferably, however, the porous powdered explosive comprises PETN.

When used in the practise of the present invention, the relatively large particle size of the porous powdered explosive creates sufficient interstitial spaces to allow the high-burn-rate pressurizing initiator to be located within the interstitial spaces even when the mixture is pressed to a desired density within the detonator. Thus, the term "porous" is used to describe a feature of a material to form significant amounts of interstitial spaces contained within the material. A preferred level of porosity is such that the porous, powdered explosive contains, when pressed into place, void spaces of up to 30%, by volume, and more preferably, between 15 and 30% by volume void space.

Further, the shape of the crystals of the porous powdered explosive can also influence the level of interstitial spaces, and thus influence its ultimate reaction properties. For example, a cylindrical configuration would typically allow for the void spaces to have a longer continuous volume when compared to a spherical configuration. Accordingly, cylindrical, prismatic, or generally non-spherical configurations are preferred to spherical or cubic configurations since the void space in the porous powdered explosive would be relatively larger for these configurations. Accordingly, it is preferred that the porous powdered explosive be cylindrical or prismatic in shape and have a crystal aspect ratio of length to width, of at least 3 to 1, and more preferably at least 4 to 1.

As previously stated, the porous powdered explosive is also relatively large when compared with the particle size of the high-burn-rate pressurising initiator. As a general guideline, it is preferred that the crystal particle size of the porous powdered explosive is greater than 10 times, on average, of the size of the high-burn-rate initiator. Further, it is preferred that the porous powdered explosive

- 11 -

When present, the transition portion of the initiating element is located between the initiation portion and the base charge (also when present) or the closed end of the detonator. The transition portion is typically a secondary explosive which can be detonated by the reaction front passing through the initiation portion and which can detonate with sufficient energy to detonate the adjacent base charge material. The transition portion may comprise PETN, RDX, HMX, Tetryl or a mixture thereof. A preferred material for use as the transition portion is PETN having a particle size of between 75 and 185 microns, and which has a lower density than the base charge. Preferred densities for the initiation portion are between 1.0 and 1.2 g/cc.

In a further aspect, the present invention also provides a composition suitable for use in an explosive detonator which comprises an intimate mixture of a porous powdered explosive having interstitial spaces, and a high-burn-rate pressurizing initiator located within said interstitial spaces.

In a still further aspect, the present invention also provides an initiating element comprising an initiation portion and optionally a transition portion characterized in that said initiation portion comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size, high-burn-rate pressurizing initiator located within said interstitial spaces.

In a yet still further aspect, the present invention also provides a method of production of the detonators described. Further, the present invention also provides a method of blasting comprising initiating an explosive charge using a detonator, wherein the detonator is as described hereinabove with respect to the present invention.

Further objects and advantages of the present invention will be evident from the detailed description of the invention hereinbelow.

Other additional materials which may be included in the intimate mixture include materials such as explosives, pyrotechnics or propellants. Further, materials such as organic fuels, "inert" organic binders, and the like, which may or may not be consumed during the reaction/detonation may also be present.

- 5 However, preferably the levels of these additional materials is less than 25%, more preferably less than 10% and most preferably, less than 2% of the total weight of the porous, powdered explosive, the high-burn-rate pressurising initiator, and the additional material(s).

- 10 The additional material can include any suitable primary or secondary explosive or initiator which is added to modify the reaction characteristics of the initiation portion, but which does not meet the criteria of being either a porous, powdered explosive or a high-burn-rate pressurising explosive. This can include, for example, materials such as lead azide, or PETN of non-acceptable particle size (e.g. less than 100 microns). However, in light of the stated goal of
- 15 minimizing the use of a primary explosive, it is preferred that the initiation portion be essentially free of added primary explosives.

- A preferred additional material which may be used in combination with the initiation portion is a material which is a "molecular" explosive. Preferred molecular explosives are generally secondary explosive compounds wherein the
- 20 fuel and oxygen are present on the same molecule. Examples of preferred suitable secondary molecular explosives are non-acceptable particle sized PETN, RDX or HMX or mixtures thereof.

- The level of these materials should, however, be low enough so as to not interfere with the intimate mixing of the initiation portion, and thereby interfere
- 25 with the ability to locate the high-burn-rate pressuring initiator within the interstitial spaces of the porous, powdered explosive.

- Examples of other optional additional materials which may be incorporated into the initiation portion include fuels (typically organic fuels) such as finely divided solids including sulphur or carbonaceous materials such as gilsonite,
- 30 comminuted coke or charcoal, carbon black, resin acids, sugars such as glucose or dextrose and other vegetable products such as starch, nut meal, grain meal and wood pulp; and

- 17 -

With exception of the DDT element, in general, and the composition of the initiating element, in particular, production of the detonators of the present invention is essentially identical to prior art techniques. These techniques for production are well known to those skilled in the art. Using known techniques, all or a portion of the initiating element components may be added to the detonator shell with the confinement sleeve, and pressed to the desired density. Alternatively, all or a portion of the initiating element components may first be pressed into the confinement sleeve prior to inserting the sleeve into the detonator shell.

The addition of a delay element to provide a delay detonator should have little or no impact on the operation of the detonators of the present invention, and manufacture of the delay element is a standard technique in the explosive detonator technology.

The detonator igniting device can be any suitable device which will initiate the delay element and/or directly initiate the initiation portion. Suitable igniting devices include electric "matches", bridge wires, shock tube, safety fuse, detonating cord, or the like, which are inserted into the open end of the detonator shell and which are capable of generating a flame and/or shock wave. Other devices which may be included as igniting devices in the detonators of the present invention include electronic detonator "hotspots", "slapper" detonators, lasers which are capable of generating an energy pulse through, for example, a fibre optic cable, and the like. Typically, the detonator comprises an electronic detonator.

As previously discussed, a benefit of using the formulations of the present invention is that the initiating element is able to make the transition from deflagration to detonation in a standard thin wall detonator with limited levels of confinement, and do not require additional heavy confinement means, such as heavy walled steel or copper sleeves and the like. Use of these simpler

- 18 -

confinement means is preferable to the confinement means described in the DDT prior art. This improvement provides manufacturing advantages since the design of the detonator may be essentially the same as for prior art detonators. The only significant difference is the replacement of the primary explosive by a simple
5 cylindrical DDT initiating element which can be manufactured using processes similar to known processes such as, the processes used to produce rigid technology delay elements.

A preferred formulation for the initiation portion of the initiating element, according to the present invention, for use in both surface or in-hole detonators
10 comprises a mixture of a material having a high burn rate at low pressure, such as 5 to 15% potassium picrate, 5 to 15% of an oxidiser, such as potassium perchlorate which together form the pressurising initiator and 70% to 90% PETN. In this embodiment, the preferred particle size of the materials is as follows: (i) potassium picrate – between 0.5 and 3 microns; (ii) potassium perchlorate –
15 between 1 and 10 microns; and (iii) PETN – between 80 and 120 microns.

It may also be necessary, as is common in this art, to adjust the density of the initiation portion by pressing the mixture during production. Preferably, the density of the initiation portion after pressing is between 1.2 and 1.5 g/cc. However, this may vary depending on the materials selected for production of the
20 initiation portion and may vary depending on the level of confinement selected.

A preferred formulation for the transition portion of the initiating element is the use of PETN having a particle size of between 75 and 180 microns, with a number average particle size of at least 100 microns, and pressing to a density of 1.0 to 1.2 g/cc.

25 This combined initiating element formulation has demonstrated the ability to produce detonators having properties which are generally equivalent to prior art detonators containing primary explosives. However, a feature of the initiating element of the present invention is that the energy output and VOD, as well as

- 18A -

other properties such as sensitivity, heat stability, and the like may be adjusted or modified by changes to the initiating element formulations

- Preferably, the initiating element is formulated to provide acceptable performance standards over a wide temperature range from at least -40°C to
- 5 greater than 120°C. Also, it is preferred that the initiating element be formulated so as to be of roughly equivalent length to the initiation portions of prior art detonators. This may be, for example, a length of about 15 to 18 mm but this can vary depending on the detonator design. This permits the detonators produced in

- 31 -

CLAIMS:

1. A detonator comprising:
- 5 (i) a hollow detonator shell having an open end and a closed end;
- (ii) an igniting device at the open end of said shell;
- (iii) optionally a delay element adjacent said igniting device;
- (iv) an initiating element comprising an initiation portion and optionally a transition portion; and
- 10 (v) optionally a base charge.
- characterized in that said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size, high burn-rate pressurising initiator located within said interstitial
- 15 spaces.
2. A detonator as claimed in Claim 1 wherein said porous powdered explosive comprises PETN, RDX, HMX, Tetryl, TNT or a mixture thereof.
3. A detonator as claimed in Claim 2 wherein said porous powdered
- 20 explosive comprises PETN.
4. A detonator as claimed in Claim 3 wherein said PETN has a number average particle size of greater than 100 microns.
5. A detonator as claimed in Claim 1 wherein said high burn-rate pressurising initiator is selected from the group consisting of potassium picrate,
- 25 potassium styphnate, lead styphnate, potassium trinitrobenzoate, alkali or alkaline earth metal salts of nitro-aromatic compounds, and mixtures thereof.
6. A detonator as claimed in Claim 5 wherein said high burn-rate pressurising initiator is potassium picrate.

- 32 -

7. A detonator as claimed in Claim 1 wherein said high burn-rate pressurising initiator comprises a mixture of two separate components, namely a material having a high burn rate at low pressure and an oxidizer.

8. A detonator as claimed in Claim 7 wherein said oxidizer comprises
5 potassium perchlorate or ammonium perchlorate.

9. A detonator as claimed in Claim 8 wherein said oxidizer comprises potassium perchlorate.

10. A detonator as claimed in Claim 1 wherein said initiation portion comprises between 5 and 15% by weight of said oxidizer and between 5 and 15%
10 by weight of a material having a high burn rate at low pressure, which together form said pressurising initiator, and 70 to 90% by weight of said porous powdered explosive.

11. A detonator as claimed in Claim 1 wherein said transition portion
comprises PETN, RDX, HMX, Tetryl or a mixture thereof.

12. A detonator as claimed in Claim 11 wherein said transition portion
15 comprises PETN.

13. A detonator as claimed in Claim 12 wherein said PETN is pressed to a density of between 1.0 and 1.2 g/cc.

14. A detonator as claimed in Claim 1 wherein said confinement sleeve
20 is a steel, copper or stainless steel sleeve.

15. A detonator as claimed in Claim 14 wherein said confinement sleeve is a circular sleeve having a wall thickness of between 0.1 and 1.5mm.

16. A detonator as claimed in Claim 1 wherein said initiation portion comprises a mixture of 5 to 15% by weight potassium picrate having a number
25 average particle size of less than 10 microns, 5 to 15% by weight potassium perchlorate having a particle size of less than 10 microns, and 70 to 90% by

- 33 -

weight PETN having a particle size of greater than 100 microns, and wherein said initiation portion has been pressed into a confinement sleeve so as to have a density of between 1.2 and 1.5 g/cc.

17. A detonator as claimed in Claim 16 wherein said transition portion
5 comprises PETN having a particle size of greater than 100 microns and has been pressed into a confinement sleeve so as to have a density of between 1.0 and 1.2 g/cc.

18. A detonator as claimed in Claim 1 wherein said initiation portion
comprises additional components selected from the group consisting of
10 explosives, propellants, gas-generating compounds, organic fuels, binders and combinations thereof.

19. A detonator as claimed in Claim 1 wherein said igniting device
comprises a flame and/or shock wave from an electric match, a bridge wire, a
shock tube, a safety fuse or a detonating cord which is inserted into the open end
15 of the detonator shell.

20. A detonator as claimed in Claim 1 wherein said detonator comprises
an electronic detonator.

21. A detonator as claimed in Claim 1 which is essentially free of added
primary explosives.

22. A detonator as claimed in Claim 1 comprising a delay element
20 adjacent said igniting device, so as to form a delay detonator.

23. A detonator as claimed in Claim 1 wherein said detonator is impact
resistant.

24. A detonator as claimed in Claim 1 wherein said detonator is
25 propagation resistant.

25. An in-hole detonator comprising:

- 34 -

- 5 (i) a hollow detonator shell having an open end and a closed end;
(ii) an igniting device at the open end of said shell;
(iii) optionally a delay element adjacent said igniting device;
(iv) an initiating element comprising an initiation portion adjacent said delay element or said igniting device, and optionally a transition portion; and
(v) a base charge,

10 characterized in that said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size, high burn-rate pressurising initiator located within said interstitial spaces.

26. A surface detonator comprising:
15 (i) a hollow detonator shell having an open end and a closed end;
(ii) an igniting device at the open end of said shell;
(iii) optionally a delay element adjacent said igniting device; and
(iv) an initiating element comprising an initiation portion adjacent
20 said delay element or said igniting device, and optionally a transition portion,

characterized in that said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small
25 particle size, high burn-rate pressurising initiator located within said interstitial spaces.

27. A surface detonator comprising:
30 (i) a hollow detonator shell having an open end and a closed end;
(ii) an igniting device at the open end of said shell;

- 35 -

- (iii) optionally a delay element adjacent said igniting device; and
- (iv) an initiating element comprising an initiating portion adjacent said delay element or said igniting device,

5 characterized in that said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size, high burn-rate pressurising initiator located within said interstitial spaces, and wherein said initiation portion achieves only a low order detonation.

10 28. A surface detonator as claimed in Claim 26 or 27 wherein said detonator additionally comprises a base charge, and wherein the shock wave produced by said base charge is reduced by using a diluted base charge or a low density base charge.

15 29. An initiating element for use in a detonator comprising an initiation portion and optionally a transition portion wherein said initiation portion is at least partially contained within a confinement sleeve and comprises an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size, high burn-rate pressurising initiator located within said interstitial spaces.

20 30. A process for manufacturing a detonator as claimed in Claim 1 comprising, in order:

- (i) optionally inserting a base charge into a detonator shell;
 - (ii) inserting an initiating element comprising an initiation portion and optionally, a transition portion, into said detonator shell;
 - (iii) optionally inserting a delay element into said detonator shell;
- 25 and

(iv) inserting an igniting device into said detonator shell;

wherein all components are operationally adjacent each other, and wherein said initiation portion comprises an intimate mixture of a relatively large particle size, porous powdered explosive having interstitial spaces, and a relatively small

- 36 -

particle size, high burn-rate pressurising initiator located within said interstitial spaces.

31. A process as claimed in Claim 30 additionally comprising the step of
5 granulating the initiation portion.

32. A process as claimed in Claim 31 wherein said initiation portion is combined with a granulating agent prior to granulation.

33. A method of blasting comprising initiation of an explosive charge utilising at least one detonator, wherein the at least one detonator is as claimed in
10 Claim 1.

34. A composition suitable for use in an explosive detonator, the composition comprising an intimate mixture of a relatively large particle size, porous, powdered explosive having interstitial spaces, and a relatively small particle size high burn rate pressurising initiator located within said interstitial
15 spaces.



Creation date: 04-20-2004
Indexing Officer: CDAVIS8 - CHLOE DAVIS
Team: OIPEBackFileIndexing
Dossier: 09830778

Legal Date: 06-07-2001

No.	Doccode	Number of pages
1	M905	1

Total number of pages: 1

Remarks:

Order of re-scan issued on